UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/273,560	03/22/1999	TAKUMI HASEGAWA	Q53743	7269

7590	04/25/2005		EXAMINER

SUGHRUE, MION, ZINN, MACPEAK & SEAS
2100 PENNSYLVANIA AVE. N.W.
WASHINGTON,, DC 200373202

THANGAVELU, KANDASAMY

ART UNIT	PAPER NUMBER
2123	

DATE MAILED: 04/25/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

-- *The MAILING DATE of this communication appears on the cover sheet with the correspondence address* --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>26 January 2005</u>.

2a)☒ This action is **FINAL.**   2b)☐ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) <u>1-4</u> is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) <u>1-4</u> is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on <u>22 March 1999</u> is/are: a)☒ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

      1.☐ Certified copies of the priority documents have been received.

      2.☐ Certified copies of the priority documents have been received in Application No. _____.

      3.☐ Copies of the certified copies of the priority documents have been received in this National Stage
application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1)☐ Notice of References Cited (PTO-892)

2)☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3)☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4)☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____ .

5)☐ Notice of Informal Patent Application (PTO-152)

6)☐ Other: _____.

DETAILED ACTION

Introduction

1.   This communication is in response to the Applicants' Amendment mailed on January 26, 2005. Claims 1-4 of the application were amended. Claims 1-4 of the application are pending. This office action is made final.

Claim Rejections - 35 USC § 112

2.   The following is a quotation of the first paragraph of 35 U.S.C. §112:

> The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

3.   Claims 1-4 are rejected under 35 U.S.C. 112, first paragraph, as containing subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

3.1   Amended claim 1 states in Paragraph 4, "when making a delay analysis of each path of the logic circuit <u>that comprises</u> said at least one circuit, a delay time is selected from said delay time information, wherein if a selected output terminal transitions from a low state to a high

state, said delay time is selected based on the input terminal whose logical transition finally

triggered said low state to high state transition of said selected output terminal according to the

logical operation information or if a selected output terminal transitions from a high state to a

low state, said delay time is selected based on the input terminal whose logical transition finally

triggered said high state to low state transition of said selected output terminal according to the

logical operation information".

The limitation, "if a selected output terminal transitions from a high state to a low state,

said delay time is selected based on the input terminal whose logical transition finally triggered

said high state to low state transition of said selected output terminal according to the logical

operation information" has not been described anywhere in the specification. This is new

material added in the amendment and not found in the original specification.

3.2   Amended claim 2 states in Paragraph 3, "when making a delay analysis of a logic circuit

that comprises circuits from said plurality of circuits, a delay time of each path between a

plurality of input terminals and a selected output terminal of said at least one circuit is selected

from said delay time information, wherein if said selected output terminal transitions from a low

state to a high state said delay time is selected based on the input terminal of said plurality of

input terminals whose logical transition finally triggered said low state to high state transition of

said selected output terminal according to the logical operation information or if said selected

output terminal transitions from a high state to a low state said delay time is selected based on

the input terminal of said plurality of input terminals whose logical transition finally triggered

said high state to low state transition of <u>said selected output terminal</u> according to the logical

operation information".

The limitation, "if said selected output terminal transitions from a high state to a low state

said delay time is selected based on the input terminal of said plurality of input terminals <u>whose</u>

<u>logical</u> transition <u>finally triggered said</u> high state to low state transition of <u>said selected output</u>

<u>terminal</u> according to the logical operation information" has not been described anywhere in the

specification. This is new material added in the amendment and not found in the original

specification.

3.3   Amended claim 3 states in Paragraph 3, "if the logic circuit comprises said at least one

circuit, selecting the delay time of each path of said at least one circuit from said delay time

information, wherein if a selected output terminal transitions from a low state to a high state, said

delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered said</u>

low state to high state transition of <u>said selected output terminal</u> according to the logical

operation information or if a selected output terminal transitions from a high state to a low state

said delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered</u>

<u>said</u> high state to low state transition of <u>said selected output terminal</u> according to the logical

operation information".

The limitation, "if a selected output terminal transitions from a high state to a low state

said delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered</u>

<u>said</u> high state to low state transition of <u>said selected output terminal</u> according to the logical

operation information" has not been described anywhere in the specification. This is new

material added in the amendment and not found in the original specification.

3.4   Amended claim 4 states in Paragraph 3, "if <u>said</u> logic circuit comprises said at least one

circuit, selecting the delay time of each path of said at least one circuit from said delay time

information, wherein if a selected output terminal transitions from a low state to a high state, said

delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered said</u>

low state to high state transition of <u>said selected output terminal</u> according to the logical

operation information, or if a selected output terminal transitions from a high state to a low state,

said delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered</u>

<u>said</u> high state to low state transition of <u>said selected output terminal</u> according to the logical

operation information".

The limitation, "if a selected output terminal transitions from a high state to a low state,

said delay time is selected based on the input terminal <u>whose logical</u> transition <u>finally triggered</u>

<u>said</u> high state to low state transition of <u>said selected output terminal</u> according to the logical

operation information" has not been described anywhere in the specification. This is new

material added in the amendment and not found in the original specification.

Claim Interpretations

4.   In Claim 1, the limitation, "if a selected output terminal transitions from a high state to a

low state, said delay time is selected based on the input terminal whose logical transition **finally**

triggered said high state to low state transition of said selected output terminal according to the

logical operation information" has been interpreted as "if a selected output terminal transitions

from a high state to a low state, said delay time is selected based on the input terminal whose

logical transition **initially** triggered said high state to low state transition of said selected output

terminal according to the logical operation information".

In Claim 2, the limitation, "if said selected output terminal transitions from a high state to

a low state said delay time is selected based on the input terminal of said plurality of input

terminals whose logical transition **finally** triggered said high state to low state transition of said

selected output terminal according to the logical operation information" has been interpreted as

"if said selected output terminal transitions from a high state to a low state said delay time is

selected based on the input terminal of said plurality of input terminals whose logical transition

initially triggered said high state to low state transition of said selected output terminal according

to the logical operation information".

In Claim 3, the limitation, "if a selected output terminal transitions from a high state to a

low state, said delay time is selected based on the input terminal whose logical transition **finally**

triggered said high state to low state transition of said selected output terminal according to the

logical operation information" has been interpreted as "if a selected output terminal transitions

from a high state to a low state, said delay time is selected based on the input terminal whose

logical transition **initially** triggered said high state to low state transition of said selected output

terminal according to the logical operation information".

In Claim 4, the limitation, "if a selected output terminal transitions from a high state to a

low state, said delay time is selected based on the input terminal whose logical transition **finally**

triggered said high state to low state transition of said selected output terminal according to the

logical operation information" has been interpreted as "if a selected output terminal transitions

from a high state to a low state, said delay time is selected based on the input terminal whose

logical transition **initially** triggered said high state to low state transition of said selected output

terminal according to the logical operation information".

Claim Rejections - 35 USC § 103

5.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.

6.   The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459

(1966), that are applied for establishing a background for determining obviousness under 35

U.S.C. 103(a) are summarized as follows:

1.   Determining the scope and contents of the prior art.
2.   Ascertaining the differences between the prior art and the claims at issue.
3.   Resolving the level of ordinary skill in the pertinent art.
4.   Considering objective evidence present in the application indicating obviousness
        or nonobviousness.

7.   Claims 1-4 are rejected under 35 U.S.C. 103(a) as being unpatentable over **Blinne et al.**

(U.S. Patent 5,274,568) in view of **Hasegawa** (U.S. Patent 6,041,168) and further in view of

Hasegawa (U.S. Patent 5,528,511).

7.1   **Blinne et al.** teaches method of estimating logic cell delay time. Specifically, as per

Claim 1, **Blinne et al.** teaches the delay analysis system for making a delay analysis of a logic

circuit (Col 1, Lines 7-13);

the system having a delay analysis library (Col 1, Lines 9-13); and

comprising connection information and delay time information for a plurality of circuits

(Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

Blinne et al. does not expressly teach that for at least one circuit of the plurality of

circuits, the library further comprises logical operation information. **Hasegawa** '168 teaches that

for at least one circuit of the plurality of circuits, the library further comprises logical operation

information (Col 1, Lines 58-61 and Col 2, Lines 31-35), as delay verification time can be

shortened and high speed delay verification achieved by calculating delay time based on logic

information, connecting information and delay information (Col 2, Lines 28-35). It would have

been obvious to one of ordinary skill in the art at the time of Applicant's invention to modify the

system of **Blinne et al.** with the system of **Hasegawa** '168 that included for at least one circuit of

the plurality of circuits, the library further comprising logical operation information, as delay

verification time could be shortened and high speed delay verification achieved by calculating

delay time based on logic information, connecting information and delay information.

Blinne et al. and **Hasegawa** '168 do not expressly teach the logical operation

information representing correspondence between logical state transitions at each input terminal

of the at least one circuit and logical state transitions at each output terminal of the at least one

circuit; and the delay information for the at least one circuit is based upon logical state transitions

at the input terminals and corresponding logical state transitions at the output terminals as

represented by the logical operation information for the at least one circuit. **Hasegawa** '511

teaches the logical operation information representing correspondence between logical state

transitions at each input terminal of the at least one circuit and logical state transitions at each

output terminal of the at least one circuit; and the delay information for the at least one circuit is

based upon logical state transitions at the input terminals and corresponding logical state

transitions at the output terminals as represented by the logical operation information for the at

least one circuit (Fig. 3; Col 1, Lines 28-35; Col 2, Lines 30-42; Col 3, Lines 5-26; Fig. 3 shows

the logical state transitions at each input terminal and logical state transitions at each output

terminal; Col 1, Lines 28-35 discusses the logical state transitions at the input terminal and the

output terminal, using rise/fall terms; Col 2, Lines 30-42 states that the delay time of the upper

route having larger delay has no effect on the determination of the delay time of the OR gate

(invalid); it is clear that the logical operation information is stored in the computer (library)

representing correspondence between logical state transitions at each input terminal of the at

least one circuit and logical state transitions at each output terminal of the at least one circuit;

Col 3, Lines 5-26 describes that the delay time information is stored for each rise/fall type signal

at various input and output nodes, an arc with invalid rise/fall signal is invalidated and the delay

time is obtained for the logic circuit after the arcs are modified), as this provides correct delay

time even when either of rise or fall of the signal has no effect in a delay time computation

process (Col 2, Lines 61-65). It would have been obvious to one of ordinary skill in the art at the

time of Applicant's invention to modify the system of **Blinne et al.** and **Hasegawa** '168 with the

system of **Hasegawa** '511 that included the logical operation information representing

correspondence between logical state transitions at each input terminal of the at least one circuit

and logical state transitions at each output terminal of the at least one circuit; and the delay

information for the at least one circuit being based upon logical state transitions at the input

terminals and corresponding logical state transitions at the output terminals as represented by the

logical operation information for the at least one circuit. The artisan would have been motivated

because this would provide correct delay time even when either of rise or fall of the signal had

no effect in a delay time computation process.

Blinne et al. does not expressly teach that when making a delay analysis of each path of

the logic circuit that comprises the at least one circuit, a delay time is selected from the delay

time information, wherein if a selected output terminal transitions from a low state to a high

state, the delay time is selected based on the input terminal whose logical transition finally

triggered the low state to high state transition of the selected output terminal according to the

logical operation information or if a selected output terminal transitions from a high state to a

low state, the delay time is selected based on the input terminal whose logical transition **initially**

triggered the high state to low state transition of the selected output terminal according to the

logical operation information. **Hasegawa** '511 teaches that how when making a delay analysis

of each path of the logic circuit that comprises the at least one circuit, if an OR gate is used, a

delay time is selected from the delay time information, wherein if a selected output terminal

transitions from a low state to a high state, the delay time is selected based on the input terminal

whose logical transition **initially** triggered the low state to high state transition of the selected

output terminal according to the logical operation information or if a selected output terminal

transitions from a high state to a low state, the delay time is selected based on the input terminal

whose logical transition **finally** triggered the high state to low state transition of the selected

output terminal according to the logical operation information (CL1, L28-35; Col 2, Lines 30-42;

Col 3, Lines 5-26), as this provides correct delay time even when either of rise or fall of the

signal has no effect in a delay time computation process (Col 2, Lines 61-65). It would have

been obvious to one of ordinary skill in the art at the time of Applicant's invention to modify the

system of **Blinne et al.** with the system of **Hasegawa** '511 and include an AND gate in the place

of an OR gate, so when making a delay analysis of each path of the logic circuit that comprises

the at least one circuit, a delay time is selected from the delay time information, wherein if a

selected output terminal transitions from a low state to a high state, the delay time is selected

based on the input terminal whose logical transition finally triggered the low state to high state

transition of the selected output terminal according to the logical operation information or if a

selected output terminal transitions from a high state to a low state, the delay time is selected

based on the input terminal whose logical transition **initially** triggered the high state to low state

transition of the selected output terminal according to the logical operation information. The

artisan would have been motivated because this would provide correct delay time even when

either of rise or fall of the signal had no effect in a delay time computation process.

7.2   As per Claim 2, **Blinne et al.** teaches the delay analysis system for making a delay

analysis of a logic circuit (Col 1, Lines 7-13);

        the system having a delay analysis library (Col 1, Lines 9-13); and

        comprising connection information and delay time information for a plurality of circuits

(Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

        Blinne et al. does not expressly teach that for each of the plurality of circuits, the library

further comprises logical operation information. **Hasegawa** '168 teaches that for each of the

plurality of circuits, the library further comprises logical operation information (Col 1, Lines 58-61 and Col 2, Lines 31-35), as delay verification time can be shortened and high speed delay verification achieved by calculating delay time based on logic information, connecting information and delay information (Col 2, Lines 28-35). It would have been obvious to one of ordinary skill in the art at the time of Applicant's invention to modify the system of **Blinne et al.** with the system of **Hasegawa** '168 that included for each of the plurality of circuits, the library further comprising logical operation information, as delay verification time could be shortened and high speed delay verification achieved by calculating delay time based on logic information, connecting information and delay information.

Blinne et al. and **Hasegawa** '168 do not expressly teach the logical operation information representing correspondence between logical state transitions at each input terminal and logical state transitions at each output terminal for each circuit of the plurality of circuits, and the delay information for the at least one circuit is based upon logical state transitions at the input terminals and corresponding logical state transitions at the output terminals as represented by the logical operation information for the at least one circuit. **Hasegawa** '511 teaches the logical operation information representing correspondence between logical state transitions at each input terminal and logical state transitions at each output terminal for each circuit of the plurality of circuits, and the delay information for the at least one circuit is based upon logical state transitions at the input terminals and corresponding logical state transitions at the output terminals as represented by the logical operation information for the at least one circuit (Fig. 3; Col 1, Lines 28-35; Col 2, Lines 30-42; Col 3, Lines 5-26; Fig. 3 shows the logical state transitions at each input terminal and logical state transitions at each output terminal; Col 1,

Lines 28-35 discusses the logical state transitions at the input terminal and the output terminal,
using rise/fall terms; Col 2, Lines 30-42 states that the delay time of the upper route having
larger delay has no effect on the determination of the delay time of the OR gate (invalid); it is
clear that the logical operation information is stored in the computer (library) representing
correspondence between logical state transitions at each input terminal of the at least one circuit
and logical state transitions at each output terminal of the at least one circuit; Col 3, Lines 5-26
describes that the delay time information is stored for each rise/fall type signal at various input
and output nodes, an arc with invalid rise/fall signal is invalidated and the delay time is obtained
for the logic circuit after the arcs are modified), as this provides correct delay time even when
either of rise or fall of the signal has no effect in a delay time computation process (Col 2, Lines
61-65). It would have been obvious to one of ordinary skill in the art at the time of Applicant's
invention to modify the system of **Blinne et al.** and **Hasegawa** '168 with the system of
Hasegawa '511 that included the logical operation information representing correspondence
between logical state transitions at each input terminal and logical state transitions at each output
terminal for each circuit of the plurality of circuits, and the delay information for the at least one
circuit being based upon logical state transitions at the input terminals and corresponding logical
state transitions at the output terminals as represented by the logical operation information for the
at least one circuit. The artisan would have been motivated because this would provide correct
delay time even when either of rise or fall of the signal had no effect in a delay time computation
process.

       Blinne et al. does not expressly teach that when making a delay analysis of a logic circuit
that comprises circuits from the plurality of circuits, a delay time of each path between a

plurality of input terminals and a selected output terminal of the at least one circuit is selected

from the delay time information, wherein if the selected output terminal transitions from a low

state to a high state the delay time is selected based on the input terminal of the plurality of input

terminals whose logical transition finally triggered the low state to high state transition of the

selected output terminal according to the logical operation information or if the selected output

terminal transitions from a high state to a low state the delay time is selected based on the input

terminal of the plurality of input terminals whose logical transition **initially** triggered the high

state to low state transition of the selected output terminal according to the logical operation

information. **Hasegawa '511** teaches that how when making a delay analysis of a logic circuit

that comprises circuits from the plurality of circuits, if an OR gate is used, a delay time of each

path between a plurality of input terminals and a selected output terminal of the at least one

circuit is selected from the delay time information, wherein if the selected output terminal

transitions from a low state to a high state the delay time is selected based on the input terminal

of the plurality of input terminals whose logical transition **initially** triggered the low state to high

state transition of the selected output terminal according to the logical operation information or if

the selected output terminal transitions from a high state to a low state the delay time is selected

based on the input terminal of the plurality of input terminals whose logical transition **finally**

triggered the high state to low state transition of the selected output terminal according to the

logical operation information (CL1, L28-35; Col 2, Lines 30-42; Col 3, Lines 5-26), as this

provides correct delay time even when either of rise or fall of the signal has no effect in a delay

time computation process (Col 2, Lines 61-65). It would have been obvious to one of ordinary

skill in the art at the time of Applicant's invention to modify the system of **Blinne et al.** with the

system of **Hasegawa** '511 and include an AND gate in the place of an OR gate, so when making

a delay analysis of a logic circuit that comprises circuits from the plurality of circuits, a delay

time of each path between a plurality of input terminals and a selected output terminal of the at

least one circuit is selected from the delay time information, wherein if the selected output

terminal transitions from a low state to a high state the delay time is selected based on the input

terminal of the plurality of input terminals whose logical transition finally triggered the low state

to high state transition of the selected output terminal according to the logical operation

information or if the selected output terminal transitions from a high state to a low state the delay

time is selected based on the input terminal of the plurality of input terminals whose logical

transition **initially** triggered the high state to low state transition of the selected output terminal

according to the logical operation information. The artisan would have been motivated because

this would provide correct delay time even when either of rise or fall of the signal had no effect

in a delay time computation process.

7.3   As per Claim 3, **Blinne et al.** teaches a method for making a delay analysis of a logic

circuit (Col 1, Lines 7-13); comprising the steps of:

        referencing a delay analysis library for a plurality of circuits (Col 1, Lines 9-13);

        the delay analysis library comprising connection information, delay time information

(Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

        Blinne et al. does not expressly teach the delay analysis library comprising logic

operation information. **Hasegawa** '168 teaches library comprising logic operation information

(Col 1, Lines 58-61 and Col 2, Lines 31-35), as delay verification time can be shortened and high

speed delay verification achieved by calculating delay time based on logic information,

connecting information and delay information (Col 2, Lines 28-35). It would have been obvious

to one of ordinary skill in the art at the time of Applicant's invention to modify the method of

Blinne et al. with the method of **Hasegawa** '168 that included the library comprising logic

operation information, as delay verification time could be shortened and high speed delay

verification achieved by calculating delay time based on logic information, connecting

information and delay information.

      Blinne et al. and **Hasegawa** '168 do not expressly teach the logic operation information

representing correspondence between logical state transitions at each input terminal and logical

state transitions at each output terminal for at least one circuit of the plurality of circuits; and the

delay information for the at least one circuit is based upon logical state transitions at the input

terminals and corresponding logical state transitions at the output terminals as represented by the

logical operation information for the at least one circuit. **Hasegawa** '511 teaches the logic

operation information representing correspondence between logical state transitions at each input

terminal and logical state transitions at each output terminal for at least one circuit of the

plurality of circuits; and the delay information for the at least one circuit is based upon logical

state transitions at the input terminals and corresponding logical state transitions at the output

terminals as represented by the logical operation information for the at least one circuit (Fig. 3;

Col 1, Lines 28-35; Col 2, Lines 30-42; Col 3, Lines 5-26; Fig. 3 shows the logical state

transitions at each input terminal and logical state transitions at each output terminal; Col 1,

Lines 28-35 discusses the logical state transitions at the input terminal and the output terminal,

using rise/fall terms; Col 2, Lines 30-42 states that the delay time of the upper route having

larger delay has no effect on the determination of the delay time of the OR gate (invalid); it is

clear that the logical operation information is stored in the computer (library) representing

correspondence between logical state transitions at each input terminal of the at least one circuit

and logical state transitions at each output terminal of the at least one circuit; Col 3, Lines 5-26

describes that the delay time information is stored for each rise/fall type signal at various input

and output nodes, an arc with invalid rise/fall signal is invalidated and the delay time is obtained

for the logic circuit after the arcs are modified), as this provides correct delay time even when

either of rise or fall of the signal has no effect in a delay time computation process (Col 2, Lines

61-65). It would have been obvious to one of ordinary skill in the art at the time of Applicant's

invention to modify the system of **Blinne et al.** and **Hasegawa** '168 with the system of

Hasegawa '511 that included the logic operation information representing correspondence

between logical state transitions at each input terminal and logical state transitions at each output

terminal for at least one circuit of the plurality of circuits; and the delay information for the at

least one circuit being based upon logical state transitions at the input terminals and

corresponding logical state transitions at the output terminals as represented by the logical

operation information for the at least one circuit. The artisan would have been motivated

because this would provide correct delay time even when either of rise or fall of the signal had

no effect in a delay time computation process.

   Blinne et al. does not expressly teach if the logic circuit comprises the at least one

circuit, selecting the delay time of each path of the at least one circuit from the delay time

information, wherein if a selected output terminal transitions from a low state to a high state, the

delay time is selected based on the input terminal whose logical transition finally triggered the

low state to high state transition of the selected output terminal according to the logical operation

information or if a selected output terminal transitions from a high state to a low state the delay

time is selected based on the input terminal whose logical transition **initially** triggered the high

state to low state transition of the selected output terminal according to the logical operation

information. **Hasegawa** '511 teaches if the logic circuit comprises the at least one circuit, and if

an OR gate is used, selecting the delay time of each path of the at least one circuit from the delay

time information, wherein if a selected output terminal transitions from a low state to a high

state, the delay time is selected based on the input terminal whose logical transition **initially**

triggered the low state to high state transition of the selected output terminal according to the

logical operation information or if a selected output terminal transitions from a high state to a

low state the delay time is selected based on the input terminal whose logical transition **finally**

triggered the high state to low state transition of the selected output terminal according to the

logical operation information (CL1, L28-35; Col 2, Lines 30-42; Col 3, Lines 5-26), as this

provides correct delay time even when either of rise or fall of the signal has no effect in a delay

time computation process (Col 2, Lines 61-65). It would have been obvious to one of ordinary

skill in the art at the time of Applicant's invention to modify the system of **Blinne et al.** with the

system of **Hasegawa** '511 and include an AND gate in the place of an OR gate, so if the logic

circuit comprises the at least one circuit, selecting the delay time of each path of the at least one

circuit from the delay time information, wherein if a selected output terminal transitions from a

low state to a high state, the delay time is selected based on the input terminal whose logical

transition finally triggered the low state to high state transition of the selected output terminal

according to the logical operation information or if a selected output terminal transitions from a

high state to a low state the delay time is selected based on the input terminal whose logical

transition **initially** triggered the high state to low state transition of the selected output terminal

according to the logical operation information. The artisan would have been motivated because

this would provide correct delay time even when either of rise or fall of the signal had no effect

in a delay time computation process.

7.4   As per Claim 4, **Blinne et al.** teaches a computer-readable medium having stored thereon

a program for executing a delay analysis method for a logic circuit, the computer readable

medium causing a computer to execute the method (Col 2, Lines 42-50); wherein the method

comprises:

    referencing a delay analysis library for a plurality of circuits (Col 1, Lines 9-13);

    the delay analysis library comprising connection information, delay time information

(Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

    Blinne et al. does not expressly teach the delay analysis library comprising logic

operation information. **Hasegawa** '168 teaches that the library comprising logical operation

information (Col 1, Lines 58-61 and Col 2, Lines 31-35), as delay verification time can be

shortened and high speed delay verification achieved by calculating delay time based on logic

information, connecting information and delay information (Col 2, Lines 28-35). It would have

been obvious to one of ordinary skill in the art at the time of Applicant's invention to modify the

computer-readable medium of **Blinne et al.** with the computer-readable medium of **Hasegawa**

'168 that included the library comprising logical operation information, as delay verification time

could be shortened and high speed delay verification achieved by calculating delay time based on

logic information, connecting information and delay information.

Blinne et al. and Hasegawa '168 do not expressly teach logic operation information

representing correspondence between logical state transitions at each input terminal and logical

state transitions at each output terminal of each one of the plurality of circuits, the delay

information for at least one circuit of the plurality of circuits is based upon logical state

transitions at the input terminals and corresponding logical state transitions at the output

terminals as represented by the logical operation information for the at least one circuit.

Hasegawa '511 teaches logic operation information representing correspondence between

logical state transitions at each input terminal and logical state transitions at each output terminal

of each one of the plurality of circuits, the delay information for at least one circuit of the

plurality of circuits is based upon logical state transitions at the input terminals and

corresponding logical state transitions at the output terminals as represented by the logical

operation information for the at least one circuit (Fig. 3; Col 1, Lines 28-35; Col 2, Lines 30-42;

Col 3, Lines 5-26; Fig. 3 shows the logical state transitions at each input terminal and logical

state transitions at each output terminal; Col 1, Lines 28-35 discusses the logical state transitions

at the input terminal and the output terminal, using rise/fall terms; Col 2, Lines 30-42 states that

the delay time of the upper route having larger delay has no effect on the determination of the

delay time of the OR gate (invalid); it is clear that the logical operation information is stored in

the computer (library) representing correspondence between logical state transitions at each input

terminal of the at least one circuit and logical state transitions at each output terminal of the at

least one circuit; Col 3, Lines 5-26 describes that the delay time information is stored for each

rise/fall type signal at various input and output nodes, an arc with invalid rise/fall signal is

invalidated and the delay time is obtained for the logic circuit after the arcs are modified), as this

provides correct delay time even when either of rise or fall of the signal has no effect in a delay

time computation process (Col 2, Lines 61-65). It would have been obvious to one of ordinary

skill in the art at the time of Applicant's invention to modify the system of **Blinne et al.** and

Hasegawa '168 with the system of **Hasegawa** '511 that included logic operation information

representing correspondence between logical state transitions at each input terminal and logical

state transitions at each output terminal of each one of the plurality of circuits, the delay

information for at least one circuit of the plurality of circuits being based upon logical state

transitions at the input terminals and corresponding logical state transitions at the output

terminals as represented by the logical operation information for the at least one circuit. The

artisan would have been motivated because this would provide correct delay time even when

either of rise or fall of the signal had no effect in a delay time computation process.

    Blinne et al. does not expressly teach if the logic circuit comprises the at least one

circuit, selecting the delay time of each path of the at least one circuit from the delay time

information, wherein if a selected output terminal transitions from a low state to a high state, the

delay time is selected based on the input terminal whose logical transition finally triggered the

low state to high state transition of the selected output terminal according to the logical operation

information, or if a selected output terminal transitions from a high state to a low state, the delay

time is selected based on the input terminal whose logical transition **initially** triggered the high

state to low state transition of the selected output terminal according to the logical operation

information. **Hasegawa** '511 teaches if the logic circuit comprises the at least one circuit, and if

an OR gate is used, selecting the delay time of each path of the at least one circuit from the delay

time information, wherein if a selected output terminal transitions from a low state to a high

state, the delay time is selected based on the input terminal whose logical transition **initially** triggered the low state to high state transition of the selected output terminal according to the logical operation information, or if a selected output terminal transitions from a high state to a low state, the delay time is selected based on the input terminal whose logical transition **finally** triggered the high state to low state transition of the selected output terminal according to the logical operation information (CL1, L28-35; Col 2, Lines 30-42; Col 3, Lines 5-26), as this provides correct delay time even when either of rise or fall of the signal has no effect in a delay time computation process (Col 2, Lines 61-65). It would have been obvious to one of ordinary skill in the art at the time of Applicant's invention to modify the system of **Blinne et al.** with the system of **Hasegawa '511** and include an AND gate in the place of an OR gate, so if the logic circuit comprises the at least one circuit, selecting the delay time of each path of the at least one circuit from the delay time information, wherein if a selected output terminal transitions from a low state to a high state, the delay time is selected based on the input terminal whose logical transition finally triggered the low state to high state transition of the selected output terminal according to the logical operation information, or if a selected output terminal transitions from a high state to a low state, the delay time is selected based on the input terminal whose logical transition **initially** triggered the high state to low state transition of the selected output terminal according to the logical operation information. The artisan would have been motivated because this would provide correct delay time even when either of rise or fall of the signal had no effect in a delay time computation process.

Blinne et al. does not expressly teach performing a delay calculation to determine a propagation delay time using the selected delay time of the at least one circuit. **Hasegawa '511**

teaches performing a delay calculation to determine a propagation delay time using the selected

delay time of the at least one circuit (Col 3, Lines 5-26), as this provides correct delay time even

when either of rise or fall of the signal has no effect in a delay time computation process (Col 2,

Lines 61-65). It would have been obvious to one of ordinary skill in the art at the time of

Applicant's invention to modify the computer-readable medium having stored thereon a program

of **Blinne et al.** with the computer-readable medium having stored thereon a program of

Hasegawa '511 that included performing a delay calculation to determine a propagation delay

time using the selected delay time of the at least one circuit, as this would provide correct delay

time even when either of rise or fall of the signal had no effect in a delay time computation

process.

Response to Amendments

8.   Applicants' amendments, filed on August 19, 2004 have been considered. Applicant's

arguments with respect to claim rejections under 35 USC 103 (a) are not persuasive. New claim

rejections have been included in this Office Action under 35 USC 101.

8.1   As per the applicants' argument that "With respect to claim 1, the combination of Blinne

et al., Hasegawa `168 and Hasegawa `511 fails to teach or suggest a delay analysis library

comprising delay information for a circuit that is based upon the logical state transitions at the

input and output terminals of a logical circuit, where the analysis library stores delay time

information based on correspondence between the input terminal logical state transitions and the

output terminal logical state transitions, and the delay information is selected based upon certain

input/output terminal signal transitions; the combination of Blinne et al., Hasegawa `1fi8 and

Hasegawa `511 does not use input terminal logical state transitions, output terminal logical state

transitions and delay information in the same manner as the present invention", the examiner

respectfully disagrees.

Blinne et al. teaches the delay analysis system having a delay analysis library (Col 1,

Lines 9-13), comprising connection information and delay time information for a plurality of

circuits (Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

Hasegawa '168 teaches that the library further comprises delay information (Col 1, Lines

58-61 and Col 2, Lines 31-35). **Hasegawa '168** states that high speed delay verification can be

achieved by calculating the delay time ... based on information of the circuit model such as logic

information, connecting information and delay information.

Hasegawa '511 teaches that delay information for a circuit that is based upon the logical

state transitions at the input and output terminals of a logical circuit; delay time information

based on correspondence between the input terminal logical state transitions and the output

terminal logical state transitions, and the delay information is selected based upon certain

input/output terminal signal transitions; **Hasegawa '511** does use input terminal logical state

transitions, output terminal logical state transitions and delay information in the same manner as

the present invention; (Fig. 3; Col 1, Lines 28-35; Col 2, Lines 30-42). **Hasegawa '511** teaches

that the propagation delay time for a logic circuit is arrived at using the input signal transitions

and the current logical state of the logic circuit as index to a propagation delay time that is

representative of how the logic circuit actually operates; in addition, **Hasegawa** '511 teaches that

a delay time is selected from delay time information according to input terminal and output

terminal logical state transitions, as recited in claim 1 (Col 2, Lines 30-42; Col 3, Lines 5-26).

8.2   As per the applicants' argument that "Blinne et al. do not teach or suggest determining

delay time based on the current logical state of a circuit and how the input signal transitions will

affect that logical state; Blinne et al. ignore the logic operation of the analyzed logic circuit by

independently recording each of the many inputs of the logic circuit; inputs not being measured

are fixed to a predetermined logic level while measuring the delay time of the remaining input; in

calculating the maximum delay time for the logic circuit, Blinne et al. uses the delay time of the

input with the longest delay time; for example, this delay time is longer than what would be

found in normal AND gate operation, because in that case the output falls as soon as the input

with the shortest delay time falls", the examiner takes the position that **Hasegawa** '511 teaches

determining delay time based on the current logical state of a circuit and how the input signal

transitions will affect that logical state, as explained in Paragraph 9.1 above.

8.3   As per the applicants' argument that "Hasegawa '168 does not even teach or suggest

signal transitions, but instead adds a series of maximum delay times together to determine a

propagation delay; while the circuit modeling technique disclosed by Hasegawa '511 uses rising

and falling signals, Hasegawa '511 still rely upon maximum delay times, stored in the arcs

between nodes, for propagation delay time calculations; Hasegawa '511 does not teach or

suggest determining delay time for each path based on the logical state transitions at the input

and output terminals; the Patent Office argues that Hasegawa `511 discloses the rise/fall

transitions of the invention recited in claim 1; however, Hasegawa `511 also specifies that certain

paths are "invalid" due to their rise/fall characteristics for certain signals, and that no path that

contains an "invalid" identifier is used for delay calculations; the combining of Blinne *et al.,*

Hasegawa `168 and Hasegawa `511 with each other does not remove this fundamental deficiency

which permeates each of the references; in the three references, the propagation delay time for a

logic circuit is arrived at using maximum delay times, and there is no discussion of using the

input signal transitions and the current logical state of the logic circuit as index to a propagation

delay time that is representative of how the logic circuit actually operates; moreover, the delay

analysis in Hasegawa `511 is for a single-input, single-output circuit... while claim 1 specifically

recites that the propagation analysis is made for "each path of the logic circuit that comprises

said at least one circuit"; for example, Hasegawa `511 specifies that certain paths are "invalid"

due to their rise/fall characteristics for certain signals, and that no path that contains an "invalid"

identifier is used for delay calculations; there is no teaching or suggestion in the combination of

references that indicates that non-use of "invalid" circuit paths is overcome", the examiner takes

the position that **Hasegawa** '511 teaches determining delay time based on the current logical

state of a circuit and how the input signal transitions will affect that logical state, as explained in

Paragraph 9.1 above.

8.4   As per the applicants' argument that "the combination of Blinne *et al.,* Hasegawa `168

and Hasegawa `511 fails to teach or suggest that a delay time is selected from delay time

information according to input terminal and output terminal logical state transitions, as recited in

claim 1; the Patent Office acknowledges that Blinne *et al.* fail to teach or suggest this feature of

the present invention; the Patent Office alleges that Hasegawa `511 provides the necessary

disclosure to overcome the acknowledged deficiencies of Blinne *et al.;* Hasegawa `511 does not

teach or suggest determining delay time based on the current logical state of a circuit and the

logical state transitions at the input and output terminals; instead, Hasegawa `511 uses the

maximum delay time between two nodes in performing its delay calculations, so that rising edge

signals and falling edge signals use the same estimated delay time for delay calculations; unlike

the present invention, Hasegawa `511 does not use all the types of logical state transitions

present between the input and output terminals of all paths in a logic circuit when selecting a

delay time for a particular signal propagation path through the logic circuit", the examiner

respectfully disagrees.

Blinne et al. teaches the delay analysis system having a delay analysis library (Col 1,

Lines 9-13), comprising connection information and delay time information for a plurality of

circuits (Col 1, Lines 39-40; Col 1, Lines 60-62; Col 1, Lines 45-48).

Hasegawa '168 teaches that the library further comprises delay information (Col 1, Lines

58-61 and Col 2, Lines 31-35). **Hasegawa '168** states that high speed delay verification can be

achieved by calculating the delay time ... based on information of the circuit model such as logic

information, connecting information and delay information.

Hasegawa '511 teaches that delay information for a circuit that is based upon the logical

state transitions at the input and output terminals of a logical circuit; delay time information

based on correspondence between the input terminal logical state transitions and the output

terminal logical state transitions, and the delay information is selected based upon certain

input/output terminal signal transitions; **Hasegawa** '511 does use input terminal logical state

transitions, output terminal logical state transitions and delay information in the same manner as

the present invention; (Fig. 3; Col 1, Lines 28-35; Col 2, Lines 30-42). **Hasegawa** '511 teaches

that the propagation delay time for a logic circuit is arrived at using the input signal transitions

and the current logical state of the logic circuit as index to a propagation delay time that is

representative of how the logic circuit actually operates; in addition, **Hasegawa** '511 teaches that

a delay time is selected from delay time information according to input terminal and output

terminal logical state transitions, as recited in claim 1 (Col 2, Lines 30-42; Col 3, Lines 5-26).

8.5   As per the applicants' argument that "Applicant submits that the Patent Office cannot

fulfill the "all limitations" prong of a *prima facie* case of obviousness with respect to claim 1, as

required by *In re Vaeck;* With respect to claim 2, the combination of Blinne *et* al., Hasegawa

'168 and Hasegawa '511 fails to teach or suggest a delay analysis library comprising delay time

information for a circuit that is based upon the type of logical state transitions present at the

circuit's input and output terminals as represented by stored logical operation information and the

delay information is selected based upon certain input/output terminal signal transitions. As

discussed above with respect to claim 1, the combination of Blinne *et* al., Hasegawa '168 and

Hasegawa '511 does not use the type of logical state transitions at both the input and output

terminals of a circuit in the same manner as the present invention. In addition, the combination of

Blinne et al., Hasegawa '168 and Hasegawa '511 fails to teach or suggest selecting a delay time

for each circuit path between an input terminal and an output terminal of a logic circuit from

stored delay time information according to the type of logical state transitions for the input and

output terminals. As discussed above with respect to claim 1, Hasegawa `511 specifies that

certain paths are "invalid" due to their rise/fall characteristics for certain signals, and that no path

that contains an "invalid" identifier is used for delay calculations. *See, e.g.,* col. 3, lines 17-20;

col. 4, lines 1520; col. 6, lines 13-17 and Fig. 10 of Hasegawa `511. The Patent Office

acknowledges that Blinne *et al.* fail to teach or suggest this feature of the present invention.? The

Patent Office alleges that Hasegawa `511 provides the necessary disclosure to overcome the

acknowledged deficiencies of Blinne et al. As discussed above with respect to claim 1,

Hasegawa `511 does not teach or suggest determining delay time for each circuit path based on

the type of logical state transitions present at both the input and output terminals of a logic

circuit. Instead, Hasegawa `511 uses the maximum delay time between two nodes in performing

its delay calculations, so that rising edge signals and falling edge signals use the same estimated

delay time for delay calculations. Unlike the present invention, Hasegawa `511 does not use the

type of logical state transitions for each circuit path between the input and output terminals when

selecting a delay time for a particular signal propagation path through the logic circuit. Thus,

Applicant submits that the Patent Office cannot fulfill the "all limitations" prong of a prima *facie*

case of obviousness with respect to claim 2, as required by an *re Vaeck"*, the examiner

respectfully disagrees.

Hasegawa `511 teaches determining delay time for each path based on the logical state

transitions at the input and output terminals; determining delay time based on the current logical

state of a circuit and the logical state transitions at the input and output terminals; using all the

types of logical state transitions present between the input and output terminals of all paths in a

logic circuit when selecting a delay time for a particular signal propagation path through the

logic circuit; thus (Fig. 3; Col 1, Lines 28-35 Col 2, Lines 30-42; Col 3, Lines 5-26). Therefore,

the Examiner takes the position that the "all limitations" prong of a prima facie case of

obviousness with respect to claim 1, as required by *In re Vaeck* is fulfilled.

8.6   As per the applicants' argument that "one of skill in the art would riot be motivated to

combine the three references; although the Patent Office provides a generalized motivation

analysis with respect to a delay analysis method, none of the references teaches or suggests

providing delay information for a circuit that is based upon the type of signal transitions present

at the circuit's input and output terminals as represented by stored logical operation information;

as discussed above, Blinne *et* al., Hasegawa `168 and Hasegawa `511 rely on using the maximum

delay time that is stored for a particular logic circuit when that particular logic circuit is

undergoing propagation delay analysis; ... in addition, none of the references teaches or suggests

that a delay time is selected from delay time information for each circuit path according to the

type of logical state transitions present at both the input and output terminals of a circuit, as

recited in claim 1; since none of the references teaches or suggests these features of claim 1,

Applicant submits that one of ordinary skill in the art would not have been motivated to combine

the three references; thus, Applicant submits that the Patent Office cannot fulfill the motivation

prong of a prima *facie* case of obviousness with respect to claim 1, as required by In *re*

Dembiczak and In *re Zurko*", the examiner respectfully disagrees.

The Examiner requests the applicant's attention to the reply presented in Paragraph 9.1

above. The examiner takes the position that the motivation prong of a prima facie case of

obviousness with respect to claim 1, as required by In re Dembiczak and In re Zurko is fulfilled

as explained in Paragraph 9.1 above.

Conclusion

ACTION IS FINAL

9.   Applicant's arguments with respect to claim rejections under 35 USC 103 (a) are not

persuasive. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within TWO

MONTHS of the mailing date of this final action and the advisory action is not mailed until after

the end of the THREE-MONTH shortened statutory period, then the shortened statutory period

will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

however, will the statutory period for reply expire later than SIX MONTHS from the date of this

final action.

10.   Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dr. Kandasamy Thangavelu whose telephone number is 571-272-3717. The examiner can normally be reached on Monday through Friday from 8:00 AM to 5:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Kevin Teska, can be reached on 571-272-3716. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to TC 2100 Group receptionist: 571-272-2100.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

K. Thangavelu
Art Unit 2123
April 16, 2005